

Matica XID8100: retransfer printer for your day-to day card printing demands

The perfect solution for the regular day-to-day demand to personalize of all kind of ID Cards. Due to the retransfer printing technology, the printer can print over-the-edge without any limitations to the card design and graphic layout. The proven modular concept enables the printer to follow upgrade demands at any time. As a standard, the printer is coming in a single side version, which can be upgraded with various options.

Print resolution
300 x 300 dpi.

Print on all card materials

The retransfer technology allows the printer to print on all kind of card materials, such as PVC, ABS, PET, hybrid card constructions and even Polycarbonate

Print speed
Up to 102 cards per hour (single-sided).

Change the supplies fast and simple

The lockable hopper and the front-loading system with replaceable cartridges for the ribbon and the retransfer film make changing the supplies fast and simple.

Easy and convenient to install

To connect the printer to a PC the USB and Ethernet interfaces are available as a standard. All necessary information about the printer and its status are shown on the LCD display and the settings can be altered using the 4 push buttons right below the LCD display.

The print engine is based on a metal frame chassis, hence it is a very solid and precise printing module.

The compact and attractive design make the printer fit into any office environment and offers an outstanding price / value performance.

Life time warranty for printer head

As all retransfer printers from Matica Technologies, the XID8100 comes with a life time warranty for the print head when using the proper consumables from Matica.

The XID8100 is working with the new SRT ribbon and retransfer film only.

Specifications

- **Print Method:** Dye-sublimation retransfer
- **Print Mode:** Single- or double-sided (optional) over-the-edge retransfer printing
- **Print Resolution:** 300 dpi
- **Print Speed:** Up to 102 cards per hour (single-sided)
- **Card Thickness:** 0.25 - 1.02 mm (hopper adjustment required).
- **Input Hopper Capacity:** 200 cards (0.76 mm)
- **Output Hopper Capacity:** 100 cards (0.76 mm)
- **Interface:** USB 2.0 and Ethernet
- **Operating System Support:** Windows 7, 8,10 (32 & 64bits).
- **Card Types:** PVC, Composite PVC, ABS, PET and Polycarbonate Cards of ISO ID -1/CR-80 size (85.60 x 53.98 mm)
- **Power Supply:** 100/120 V and 220/240 V, 50/60 Hz FCC, CE, UL, GOST-R, and CCC approved
- **Operating Environment:** 15°C to 30°C, 35% to 70%noncondensing humidity.
- **Printer Dimensions:** 343 x 322 x 360 mm (WxDxH)
- **Weight:** 13.9 kg (excluding optional built-in items)
- **Warranty:** Printer: 24 months.
- **Warranty:** Printhead: Lifetime warranty using EDIsecure® materials (other conditions apply).

Attention: The use of non-Matica brand ribbons could adversely affect the performance of your Matica hardware and void the products warranty.